

senosan[®]

Lacquered-Acryl-Glass
Glass effect surfaces



SENOSAN® *Gloss news* *for furniture design*

Glass fronts create an elegant appearance in interior design. Real glass however is a very demanding and sensitive material with regard to impact and cleaning properties.

The solution is Lacquered-Acryl-Glass from Senosan – high quality surfaces with glass effect, giving the appearance of depth with it's high gloss level. This co-extruded material combines the aesthetic advantages of real glass fronts with the processing and practical advantages of senosan® film. All in all: superb design, superb handling.

Advantages:

- Claim free processing
- Ability to be cut and drilled on site for fitting of handles
- Low in weight – flexible fitting on site
- Excellent impact strength and scratch resistance
- Easy to clean and maintain



Trend colors



For all senosan® products, before ordering please definitely ask us for an original color sample! All the colors in this brochure are given for orientation only. In no way can they be seen as legally binding! Product and color changes, all rights reserved.

Product name:

senosan® TopX Acryl Glass

Rear-side material:

senosan® Glass RS

5 trend colors available ex-stock:

white 11022, white 11045, beige 7516,
beige 7529, grey 85474

1 size:

2800 x 1300 x 2.00 mm

The 2 mm thickness creates a glass effect, optically enhanced by the milled edges. To avoid bowing/bending of the finished parts after lamination, a color matched senosan® rear-side balancing sheet material in 2 mm is available.



Technical details

Product	Finish	Scratch resistance	Gloss Level (60°)	Thickness (mm)	Color	Application
senosan® TopX Acryl Glass	Surface protection film, Corona on reverse, coating	1.1 N to IHD-W-466 Class 1	GLE ca. 90	2.00	Colored	Flat lamination
senosan® Glass RS	With 017DB embossing, Corona on reverse	–	GLE ca. 7	2.00	Colored	Flat lamination



SENOPLAST

SENOSAN

Senoplast Klepsch & Co. GmbH · Senosan GmbH
 Wilhelm-Klepsch-Straße 1 · 5721 Piesendorf · Austria
 T +43 6549 7444-0 · F +43 6549 7444-4410260
 info@senosan.com · www.senosan.com
 info@senoplast.com · www.senoplast.com

